

## Container Handler

Used Container Handler Connecticut - Also known as container ships or cargo ships, container handlers use large intermodal containers to transport their goods. This type of shipping is called containerization and it is a specific kind of freight transport that carries non-bulk types of seagoing cargo. The capacity of these specialty ships is equal to twenty-foot loads. Typical loads range with a mixture of 20-foot and 40-foot containers. Approximately ninety percent of non-bulk cargo across the globe is transported by container ships. Container handlers are one of the biggest vessels sailing and are the main rival for oil tankers on the ocean. There are two main categories for dry cargo which are break-bulk and bulk cargo. Grain and coal fall into the bulk cargo category. They are often moved in their raw form, package-free in large volumes in the hull of the ship. Break-bulk cargo typically is made up of manufactured items that are shipped in packaging. Before containerization was invented in the 50s, break-bulk items were loaded, secured and unlashd one item at a time. Grouping cargo into containers allows for 1000-3000 cubic feet of cargo to be simultaneously moved once every container has been secured with standardization techniques. Break-bulk cargo shipping has greatly increased overall efficiency. It is estimated that shipping time has been reduced by eighty-four percent and costs have been reduced by approximately thirty-five percent. More than ninety percent of non-bulk items were recorded as being transported in containers in 2001. The initial container ships in the 1940s were designed from tankers that were converted post-WWII. Container ships do not rely on individual hatches, holds and dividers that are part of regular cargo ships. The hull of the container ship is similar to a sizeable warehouse that uses vertical guide rails to divide the area into cells. These cells have been engineered to hold the cargo in containers. Most shipping containers are constructed from steel; however, additional materials including plywood, fiberglass and wood are used. As containers have been designed to completely transferred to and from coastal carriers, semi-trailers, trucks, trains and more, these containers are categorized due to their function and size. The entire shipping industry has been revolutionized by containerization, although, it did not start out in the easiest manner. At first, many companies and shippers were worried about the huge costs associated with constructing ports, railway infrastructure and the roads needed to transport items via cargo ships. Various trade unions were skeptical about huge job loss with dock and port workers based on the assumption that containers would eliminate numerous cargo handling manual jobs among ports. There was a decade of legal battles prior to the container ships starting international service. By 1966, after the first container liner service began from Rotterdam, Netherlands to the USA, cargo shipping was transformed. Container ships only take a few hours to be loaded and unloaded, compared to the days a traditional cargo vessel required. Cutting labor finances and shortened shipping times between ports has been hugely successful. It only takes a few weeks to deliver items from India to Europe and vice versa, whereas it used to take months previously. Overall, there is less damaged cargo thanks to less physical handling and reduced cargo shifting due to properly securing loads. Containers are sealed prior to shipping and opened only once they arrive at their destination, resulting in less theft and disruption. There has been greater international trade growth due to the reduced shipping expenses and travel time delivered by container ships. Cargo that was previously shipped in bags, bales, cartons, barrels or crates now arrives in sealed containers from the factory. A product code on the contents is traced with the help of computers and scanning equipment. Amazingly, technology has advanced with this accurate tracking system to be so exact that a 2-week voyage can be timed for arrival with accuracy less than 15 minutes! This time management has helped with manufacturing times and guaranteeing delivery. Sealed containers of raw materials arrive in under an hour to be used in manufacturing facilities, resulting in less inventory costs and higher accuracy. Boxes are provided by shipping companies to the exporters to facilitate loading merchandise. Materials are delivered by rail or docks or a combination of both and then loaded into container handlers. Before containerization, it would take large groups of men and many hours fitting cargo items into different holds.

The shipping industry today relies on cranes either installed on the ship or on the pier to situate containers on board. After the hull has been fully loaded, additional containers can be attached to the deck. Efficiency has been one of the main design elements for cargo ships. Break-bulk ships may carry containers. Cargo holds that have been designated to cargo ships have been specially designed to enhance the processes of loading and unloading in order to keep containers safe while crossing the seas. There is a sophisticated hatch design to allow openings from the main deck to reach the cargo hold locations. A raised steel apparatus called the hatch coaming surrounds these openings that are found along the cargo hold breadth. There are secure hatch covers situated on top of the hatch coamings. Until the 1950s, wooden boards and tarps were responsible for securing the hatches and holding down the battens. Hatch covers are made of secure metal plates and cranes are used to lift them on and off of the ship. Additional hatch models use hydraulic rams and articulated mechanisms for closing and opening. Cell guides are a necessary component in cargo ship design. Attached to the cargo hold in the ship, cell guides are vertical pieces of metal that help organize the cargo. They work by guiding containers into particular rows while loading and help to support items during travel. Since the design of the container ship utilizes cell guides in such abundance, the UN Conference on Trade and Development relies on them to separate traditional break-bulk cargo ships and container ships. To showcase a container's position on the ship, there is a cargo plan system that use three dimensions. The initial coordinate starts at the beginning of the ship and increases aft. The second coordinate is the tier. The first tier begins in the lower portion of the cargo holds with the second tier found on top of the first tier and continuing in that fashion. The row is the third coordinate. Rows are situated on the ship's port side have even numbers while those found starboard have odd numbers. The cargo situated near the centerline showcases lower numbers and as the cargo increases further from the center, the numbers get higher. It is possible for container handlers to carry twenty, forty and forty-five foot containers. The big containers will only travel and fit above deck. The forty-foot sized containers makes up ninety-percent of the shipping containers. Roughly 90% of the freight in the world is delivered via container shipping. Approximately eighty-percent of global freight is shipped via forty-foot containers.